


Cover 705LT




Carmine red
RAL 3002

705-1065



Gentian blue
RAL 5010

705-1052




Ultramarine blue
RAL 5002

705-1051



Opal green
RAL 6026

705-1055



Window grey
RAL 7040

705-1072



Jet black
RAL 9005

705-1075

Protect Cover 705LT

The market reference for a multipurpose technical cover

Main advantages

- Cold temperature resistance to -50°C (-58°F)
- Excellent lifespan
- High UV resistance
- Wide range of colours
- Long dimensional stability thanks to Precontraint® technology

Main applications

- Wintering solutions
- Low temperature tarpaulins
- Truck curtains

Technical specifications	
Yarn	1100 dtex PES HT
Coating	PVC
Finish	Acrylic varnish both sides
Weight EN ISO 2286-2	670 g/m² • 19.8 oz/sq. yd
Width EN ISO 2286-1	270 cm • 106.3 in
Roll length	Rolls: 30 lm • 32.81 yd - Jumbo rolls: 350 lm • 382.76 yd
Physical properties	
Tensile strength (warp/weft) EN ISO 1421	250/250 daN/5 cm • 562/562 lbs/2 in.
Tear strength (warp/weft) DIN 53.363	35/35 daN • 79/79 lbs
Extreme working temperatures DIN EN 1876-1	-30°C/+70°C • -22°F/+158°F
Cold crack resistance ASTM D751 1-65	-50°C • -58°F
Environmental properties	
Carbon impact EN 15804 + A1	3.36 kg CO ₂ eq./m²
Management systems	
Quality: ISO 9001 • Environment: ISO 14001 • Energy: ISO 50001	
Certifications, labels	

Precontraint® Technology



¹ Summarizes the group's CSR project focused on human, to align economic performance and positive impact.

The technical data above are average values with a +/-10% tolerance.

The purchaser of our products is responsible for their application or transformation in relation to possible third party rights. The purchaser of our products is responsible for their installation in compliance with the standards, working practices and safety regulations of their destination country. Please refer to our warranty document with regard to contractual liability.

Values quoted in this document are commonly used test results for design purposes. They are given for information only in order to offer our customers optimum usage of our products. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.

The colours and textures presented are included for information only.